

Data Sheet PalmSure Enrolment Unit

Model – PSE-2210

Optimal Palm Positioning

The PalmSure UGuide is designed for use in conjunction with Fujitsu PalmSecure OEM Sensor STD. The sensor snaps into the base of the PalmSure UGuide for easy mounting at a secure access point such as the entrance to a laboratory. The PalmSure UGuide allows users to effortlessly position their hand optimally for scanning.

Usability and Ergonomics

- Intuitive design allows users to optimally position their hands for scanning.
- Perfect for high traffic secure access points.

Quality

- Heavy duty plastic housing is designed for years of daily contact by hundreds of users.



Technical Specification

	Solid Palm guide for PalmSure(TM) Sensor
Color	Black
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Dimensions (WxDxH)	140 x 170 x 110 mm
Weight	251 g

Contents

1. Fujitsu Sensor	General Specifications Reading
a. Reading System	by near-infrared light Entire
b. Scope of Capture	Palm (excluding fingers)
c. Capturing distance	40 to 60 mm
d. Material of the surface of sensor unit	Glass
2. Usb Cable	1.5 mtr length

PalmSure Solutions Pvt. Ltd.

#3, Hemagiri, 1st Floor, 7th Main Road, Mysore Bank Colony, Banashankari 1st Stage, Bangalore-560050 Karnatka. Mobile : +91-8277107611, E-mail : sales@palmSure.com